DSD-2

240V Dry Contact Station

The Trolmaster DSD-2 Dry-Contact Station module provides a simple and flexible solution to users who want to connect & control devices to the Hydro-X using a “dry-contact” or relay
to activate the device. Some equipment requires either normally open or normally closed contact closure in order to activate the equipment. The DSD-2 is the product that you need to control those types of devices.

***Note:** The DSD-2 can be configured to work as the other Trolmaster power modules work. The DSD-2 connects to the “devices” line on the Hydro-X and can control various devices such as Lighting contactors, Light Deprivation curtains, Pump contactors, Temperature devices, Humidity devices, and CO2 devices.

*Consult Trolmaster for questions concerning your particular device.

Specifications

DSD-2

Input Voltage

Input Voltage	100-240V~, 50/60Hz

DC Output

DC Output	12V / 0.5A

NO/NC

NO/NC	6A@250VAC, 6A@30VDC

Working Environments

Temperature	32-104°F (0-40°C)
Humidity	≤90%

Package Dimensions

Size	3.35inch / 85mm (L) x 3.15inch / 80mm (W) x 3.54inch / 90mm (H)
Gross Weight	11.64oz / 330g

Package Content

Dry Contact Station	1pc
16ft RJ12 Cable	1pc
4ft RJ 12 Cable	1pc
RJ12 T-Splitter	1pc

Link Up

DSD-2

CONNECTION DIAGRAM







RoHS

© 2025 TrolMaster Agro Instruments Co., Ltd. All rights reserved.

Email: support@thinkgrow.com
Phone: 877-420-9876

verdetop
Gracias por confiar en Verdetop
Más información, fichas y asesoramiento en verdetop.com
www.verdetop.com